Safety T.E.S.T.

Task/Equipment Specific Training

Push Edger

Company Name			Instructor			Date
Recommended Personal Protective Equipment						
Safety Glasses, Hearing Protection, Gloves, Above the Ankle Lace-up Work Boots, Safety Vest (while						
working near roadways and parking lots)						
Sequence of Basic Job Steps & Potential Hazards		Pictures	Recommended Action or Procedure			
	Examine the work area and equipment before working. Stones, pine cones, sticks, or trash could injure others, yourself, or cause property damage. Slip and Falls.	ASSESSED 1	 Remove any object that can be thrown by the equipment and cause injury or property damage. Identify areas of potential slips and falls, pine straw beds, wet walkways, etc. Check the condition of the push edger. Make repairs, replace necessary parts, and tighten loose bolts before using. 			
	Fuel equipment. Fires, Splashing gas in eyes, or adding wrong fuel mixture.		 DO NOT SMOKE or have an open flame while fueling. Let equipment cool down before fueling. Remove cap carefully. Wear safety glasses when fueling. Ensure that you are using the correct fuel. 			
	Starting equipment. Slip or Falls, Strains. • Ensure • Follow • Ensure • Place • Use or steady			Ensure equipment is on level ground and will not roll. Follow owner's manual on choke and throttle positions. Ensure blades are disengaged if applicable. Place foot on equipment for balance and to secure it down. Use one arm to pull back on cord and the other should hold the equipment teady. Avoid using your back to pull.		
	Use equipment to edge. Strains/Sprains, Flying Debris, Slips, Trips, Falls, High noise levels, Vehicle Traffic, Lacerations.		 Operate the equipment with both hands. Try to avoid twisting body, and always try to push not pull equipment. Wear safety glasses and always operate with guard attached and down. Wear work boots with good tread. Pay attention to surroundings. Wet grass can be very slippery. Wear appropriate hearing protection. Always face traffic and wear high vis safety vest. Wear abrasion-resistant gloves. Watch your footing when working on slopes. When transporting form one location to another, disengage the blade. Stop operations when pedestrians are nearby. Never leave the machine running and unattended. 			
	Replacing blades/Clearing jams Lacerations, Getting fingers/hand caught in turning attachments.		 Turn off motor and ensure blades have stopped turning before replacing or clearing jams. Unplug spark plug before replacing blades. 			
	Shut down equipment. Fires from hot exhaust, Rotating attachments.	Ţ	leaves.	e exhaust from equipment near combustible material such as f blades until they stop rotating.		
Employee's Name En		Employee's Si	gnature	Employee's Nam	e	Employee's Signature



